

FIG. 1A





FIG. 1 B



2/22

FIG.2




FIG.3A




FIG.3B




FIG.3C





FIG.3D



3/22

FIG.4A





FIG.4B



4/22

FIG.5A




FIG.5B




FIG.5C





FIG.5D



6/22

FIG.7A





FIG.7B



7/22


FIG.8

Electrostatic withstand voltage
across respective terminals (unit: V)

IN — Ctl-1	700
IN — Ctl-2	700
OUT1 — Ctl-1	700
OUT2 — Ctl-2	700


FIG.9

8/22




9/22

FIG.10




10/22

FIG.11



11/22

FIG.12



12/22

FIG.13A






FIG.13B



13/22

FIG.14



14/22

FIG. 15




FIG.16A


Comparison of spreading of currents and recombination

	a-structure			b-structure-1			b-structure-2		
Electron current density	y__2	x__0	Product	y__2	x__0	Product	y__2	x__0	Product
	21.9	10.5	230.0	26	15	390.0	23.8	11.3	268.9
Hole current density	y__2	x__0		y__2	x__0		y__2	x__0	
	13.7	6	82.2	23.9	12.5	298.8	12.7	7.4	94.0
Recombination density	y__2	x__0		y__2	x__0		y__2	x__0	
	29.7	14.8	439.6	33.1	20	662.0	33.9	15.5	525.5

FIG.16B

b-structure-3		
y__2	x__0	Product
69	36.1	2490.9
y__2	x__0	
47.9	29.1	1393.9
y__2	x__0	
80 or more	43.9	3512 or more

FIG.16C



16/22

FIG. 17




FIG.18A





FIG.18B



18/22

FIG.19A





FIG.19B



19/22

FIG.20A






FIG.20B



20/22

FIG.21



21/22

FIG.22




FIG.23




FIG.24




FIG.25

Electrostatic withstand voltage
across respective terminals (unit: V)

IN — Ctl-1	140
IN — Ctl-2	140
OUT1 — Ctl-1	500
OUT2 — Ctl-2	450